



MAG 2000™

MAG 2000 KEY :

- | | | | | | |
|----|---------------------------------|----|-------------------------|----|------------------------|
| D | — Shaft Size | D3 | — Max. Gland Diameter | L2 | — Outboard Seal Length |
| D1 | — Seal Diameter in stuffing Box | D4 | — Min. Slot Bolt Circle | L3 | — Gland Width |
| D2 | — Stuffing Box Inside Diameter | L1 | — Inboard Seal Length | W | — Slot Width |

MAG 2000™ — DIMENSIONAL DATA / METRIC (mm)

Seal Code	Shaft D	D1	D2	D3	D4	L1	L2	L3	W	Bolts
2000-0040	40	73.0	80	155	125	36.5	74.5	32.5	18	4*M16
2000-0045	45	80.0	87	165	135	36.5	74.5	32.5	18	4*M16
2000-0050	50	87.0	94	175	140	36.5	74.5	32.5	18	4*M16
2000-0055	55	93.0	100	180	150	36.5	74.5	32.5	18	4*M16
2000-0060	60	93.0	100	180	150	36.5	74.5	32.5	18	4*M16
2000-0065	65	108.0	118	195	165	36.5	74.5	32.5	18	4*M16
2000-0070	70	108.0	118	195	165	36.5	74.5	32.5	18	4*M16
2000-0075	75	118.5	125	210	175	37.5	74.5	32.5	18	4*M16
2000-0080	80	118.5	125	210	175	37.5	74.5	32.5	18	4*M16
2000-0085	85	128.5	140	225	190	37.5	74.5	32.5	20	4*M18
2000-0090	90	128.5	140	225	190	37.5	74.5	32.5	20	4*M18
2000-0095	95	135.0	145	230	195	38.0	74.5	32.5	20	4*M18
2000-0100	100	145.0	150	240	205	44.5	81.5	34.0	20	4*M18
2000-0105	105	156.0	160	250	215	44.5	81.5	34.0	22	4*M20
2000-0110	110	156.0	160	250	215	44.5	81.5	34.0	22	4*M20
2000-0115	115	165.0	176	260	225	42.0	80.0	36.0	22	4*M20
2000-0120	120	165.0	176	260	225	42.0	80.0	36.0	22	4*M20
2000-0125	125	175.0	185	292	235	42.0	82.0	40.0	22	4*M20
2000-0130	130	175.0	185	292	235	42.0	82.0	40.0	22	4*M20
2000-0135	135	192.0	205	320	260	50.0	136.0	40.0	24	4*M22
2000-0140	140	192.0	205	320	260	50.0	136.0	40.0	24	4*M22
2000-0145	145	205.0	220	340	275	50.0	138.0	41.5	24	4*M22
2000-0150	150	205.0	220	340	275	50.0	138.0	41.5	24	4*M22
2000-0160	160	216.0	225	340	285	54.5	138.0	41.5	24	4*M22
2000-0170	170	226.0	235	360	295	54.5	143.0	41.5	24	6*M22
2000-0180	180	236.0	250	370	305	54.5	143.0	41.5	24	6*M22
2000-0190	190	250.0	265	385	315	54.5	143.0	41.5	24	6*M22
2000-0200	200	260.0	275	395	325	54.5	143.0	41.5	24	6*M22

© For special dimension could be manufactured and designed according to customer requirement.